

FRICKE

Landmaschinen

Fricke Landtechnik GmbH Demmin
 Klänhammer Weg 2
 17109 Demmin
 Tel: 0049 (0) 3998-2729-0
 Fax: 0049 (0) 3998272920

CLAAS Lexion 6600 m. Vario 770 ****AKTIONSPREIS!**** [191.00020.2000192]

Year of manufacture: 2023

Date: 06.06.2025

Design:

Combine harvester

Category:

Combine harvester

Power:

260 kW (354 HP)

Operating hours:

185

€ 285,000.⁰⁰

plus VAT 19% (€ 339,150.⁰⁰ Gross)



100% Gesamtzähler	
Übersicht	
Betriebsstunden	185.15 h
Arbeitszeit	135.33 h
Effektive Arbeitszeit	115.50 h
Strohhäckslerstunden	116.36 h
Fläche	497.81 ha
Strohhäcksselfläche	430.27 ha
Wegstrecke total	1107.640 km
Wegstrecke Straße	256.265 km
Wegstrecke Feld	851.375 km
Erntemenge	1650.07 t
Kraftstoffmenge total	5712.0 l
Kraftstoffmenge Straße	192.5 l
Kraftstoffmenge Feld	5519.5 l
Harnstoffmenge	166.0 l

Equipment

Description

Autocontour	✓	
On-board computer	✓	
Wide rapeseed cutter	7,70	
Width cutting unit	7,70	
State	Used	
Cabin	✓	
Air conditioning	✓	
Rapeseed cutter	✓	
Rap separator left	mechanical	
Rapeseed separator right	mechanical	
Rear tyre	500/85 R24	
Tyres in front	680/85 R32	
Rotating beacon	✓	
Cutting unit	✓	
Cutterbar trolley	✓	
Technical condition	New	
		• m. Vario 770 and transport trolley • E-channel Auto Contour chain • automatic trailer coupling • Dust extraction • Threshing drum drive 33-930 rpm • Jet Stream cleaning incl. 3D • Overflow volume measurement with Cebis display • Grain tank 11,000 litres • Grain tank outlet pipe XL • Grain tank emptying 110 l/s • Rigid outlet grommet • Standard distributor SPECIAL CUT • Swath former • 25 km/h • Mercedes Benz engine • 950 liter fuel tank • Automatic air conditioning w. heating • Cooling unit for storage box • Roller blinds for side windows • Rear camera display in the terminal • Camera AHK- Profi CAM display • Camera grain tank outlet pipe - Profi CAM • Quantimeter yield measurement • Comfort seat with air suspension • Working lighting LED plus • CEMOS AUTOMATIK- Cruise Pilot • Field Scanner Apron Sensor • Windshield washer system for side windows • Spreading deflector adjustment hydr.